

## DS10 1D Laser Omnidirectional Barcode Scanner



### Specificalton:

Perf orm anc e	Light source	650nm Laser Line		
	Scan lines	20 Laser Lines(5 directionas)		
	Scan Speed	1120 times/sec		
	Min Symbol contrast	≥25%		
	Scan Engle	Roll±360°, Skew ±60°, Pitch ±70°		
	Symbologies	EAN-8、EAN-13、EAN-13 2 add-on、EAN-13 5 add-on、ISSN、 ISBN、UPC-A、UPC-E、Code 39、Code93、Code 128、 Codabar、Interleaved 2 of 5		
	Depth of field	Tested Code	MIN	MAX
	5 mil Code 39	1cm	5cm	
	6.6 mil Code 39	1cm	11cm	

		10 mil Code 39	1cm	15cm		
		13 mil UPC	1cm	18cm		
	OS	Linux, Windows XP、7、8、10				
	Scan Mode	Auto Scan				
	Countires Keyboard	American, German, French, Japanese, Italian, Belgian, Dutch				
	Indicator	LED, BEEPER				
Env oirm ental	Drop	Withstand 5 drops from 1.5 meters				
	Sealing	IP54				
	Storage Temperature	-20-60℃				
	Operating Temperature	-10-50℃				
	Storage Humidity	5-95% Non condensing				
	Operating Humidity	5-95% Non condensing				
	Ambient Light	0-70000LUX				
Phy sica l	Net Weight	384g				
	Gross Weight	683g				
	Cable Length	180CM(±3CM)				
	Dimension	115mm*114mm*152mm				
	Packing	236mm*165mm*133mm				
	Interface	USB,RS232				
	Operating Voltage	5V				
	USB	Standby power	155mA/0.775W	RS232 2	Standby power	154mA/0.77W
		Operating Power	155mA/0.775W		Operating Power	154mA/0.77W
		Max Power	191mA/0.955W		Max Power	192mA/0.96W
Certificaiton	CE FCC RHOS					